

AC>DC UPS (Uninterruptible Power Supply)

Solis Energy's AC>DC UPS 12030 is an ideal solution to provide battery back-up power for your short-term, emergency needs. Our AC>DC UPS provides 30 watts of clean 12 volt DC, uninterrupted power to critical DC loads such as communications devices, security systems and video cameras. It is light weight enough to be mounted near the top of a streetlight or tower to power all of your applications. Engineered for fast, easy installation. RoHS compliant.

Flexibility to fit your specific requirements.

- **Truly universal to fit any input.** Auto ranging for use with 110 or 220 AC power inputs – both US and European standards.
- **Rugged and reliable NEMA 4X IP66 enclosure.** Designed for pole mounting and can just as easily be wall mounted.
- **State of the art components for the harshest of environments.** Ideal for outdoor use in areas with extreme temperature variations.

Options designed to fit your application.

- **Enclosure sunshade.** Keeps unit cooler and extends the life of the battery in tropical environments.
- **AC photocell adapter.** Provides electrical power by tapping into the electrical circuit used to power outdoor lights. Adapter inserts between the photocell and the light circuit. Cabling interconnects the power adapter to AC>DC UPS mounted near the top of the light pole.
- **Error free AC input.** Mini Change Connector for error free AC input installation
- **Error free DC output.** Micro Change Connector for error free DC output installation

Complete solution for radio deployment.



Solis Energy's 12030 Series AC>DC UPS and Streetlight Power Tap Adaptor combined to power WiFi radio.



Solis Energy's AC>DC UPS 12030 Series Specifications:

PARAMETER	DC-UPS 12030			UNIT
	Minimum	Typical	Maximum	
INPUT				
AC Input Voltage	85	—	265	Volts RMS
Input Frequency	47	—	66	Hertz
Power Factor Correction	0.95	—	—	n/a
DC Input Voltage	110	—	370	Volts
OUTPUT – Battery & Load				
Battery & Load Voltage at 25°C	13.7	13.8	13.9	Volts
Battery & Load Voltage Over 0 – 60°C (temp. comp. range)	12.9 (60°C)	—	14.9 (0°C)	Volts (ambient temp.)
Output Voltage Temperature Compensation (0 – 60°C only)	—	-0.025	—	Volts / °C
Battery Charging Current (no load)	—	—	3.6	Amps
Load Current (30 Watts)	—	—	2.16	Amps
Output Switching Noise	—	—	100	mV p-p
GENERAL				
Operating Temperature	-10	—	50	°C
Max Temperature with Derating			70	°C
Efficiency	75	—	—	%
EMC – Emissions				
Radiated Noise: 30mHz – 1gHz per FCC Class B				
Conducted Noise: 150kHz – 30mHz per FCC Class B				
PHYSICAL				
Weight		20		Lbs
Dimension	11.42" x 9.79" x 6.31".			Inches



Smart solutions for continuous outdoor power.

Solis Energy, Inc. 927 Fern Street, Suite 1200, Altamonte Springs, Florida 32701
(407) 339-6786 www.SolisEnergy.com

Copyright 2007 Solis Energy, Inc. All rights reserved. Rev 8.08